

SB-4000 WATER REPELLING INVISIBLE SEALER

Page Number: 1/3
Revision Date: 07/25/11

SECTION I - PRODUCT AND COMPANY IDENTIFICATION

Product Name: SB-4000 WATER REPELLING INVISIBLE SEALER

Company Name: SUREBOND
3925 Stern Avenue
St. Charles, IL 60174
Phone: (800) 932-3343

FOR CHEMICAL EMERGENCY CALL (800) 535-5053

PRODUCT TYPE: MASONRY SEALER
CHEMICAL FORMULA: MIXTURE
CHEMICAL NAME: SILICONE COATING

SECTION 2 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE:

Eyes: Direct contact will burn eyes.
Skin: Contact may burn skin.
Inhalation: Mist may irritate nose and throat.
Ingestion: May irritate mouth, throat and gastrointestinal tract.

HAZARD RATINGS (0-4): Fire: 0 Reactivity: 0 Toxicity: 2

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS REG#	%	TLV OSHA	TLV ACGIH
Potassium Methyl Silicate	31795-24-1	2 - 5	2 mg/m ³	2 mg/m ³

This product contains no ingredients that are listed in the SARA III, Section 313 inventory.

SECTION 4 - PHYSICAL PROPERTIES

APPEARANCE: Clear, colorless, odorless liquid
pH: 12.6
VISCOSITY: N/D
FREEZING POINT: ~ 32° F
BOILING POINT: ~ 212° F
VAPOR PRESSURE: N/D
VAPOR DENSITY: <1
SOLUBILITY IN WATER: Complete
VOLATILE (% WT): 97
SPECIFIC GRAVITY: 1.02
EVAPORATION RATE: <1
VOC: 44 g/l



SB-4000 WATER REPELLING INVISIBLE SEALER

Page Number: 3/3
Revision Date: 07/25/11

SECTION 10 - SPECIAL PROTECTION

VENTILATION TYPE:	Local exhaust.
RESPIRATORY PROTECTION:	Not needed for normal use.
PROTECTIVE GLOVES:	Rubber or plastic.
EYE PROTECTION:	Goggles or glasses with side shields.
OTHER PROTECTIVE EQUIPMENT:	None.

SECTION 11 - STORAGE AND HANDLING

Protect from freezing where possible.

SECTION 12 - SHIPPING

PROPER SHIPPING NAME: Caustic Alkali Liquids, N.O.S. (Contains Potassium Methyl Silicate)
U.S. DOT HAZARD CLASS: 8, UN1719, PG II
LABEL REQUIREMENTS: Corrosive

SECTION 13 - MISCELLANEOUS

ABBREVIATIONS:
N/A: Not applicable UNK: Unknown
N/D: Not determined
< : Less than
> : Greater than
N/E: Not established